



中再生纽维尔资源回收设备（江苏）有限公司
CHINA RECYCLING NEWELL EQUIPMENT (JIANGSU) CO.,LTD.

倾斜式龙门剪切机 *Inclined Gantry Shear*



倾斜式龙门剪切机优势 Advantages

- 配备侧压装置，料型一次剪切到位
Equipped with the side pressure device, and the type of sheared material are uniform
- 可实现连续加料，生产效率高；
Continuous feeding can be realized with high production efficiency.
- 开放式倾斜料箱，进料长度不受限制
The feeding chamber is open and inclined, making the feeding length not limited.
- 设备安装无需基础，方便移动场地
Without foundation, easy to transfer
- 智能化程度高，仅需1名操作人员
High intelligence, only 1 operator is needed.



技术参数 Specifications

序号 Number	项目 Item		CRNE-IS700	CRNE-IS1600
1	料箱尺寸（长×宽×高） Shearing box size（L*W*H）		6250*2000*2600mm	7400*2650*2250mm
2	系统工作压力 Working pressure		25MPA	28.5MPA
3	最大剪切力 Maximum shearing force		700T	1600T
4	压料长度/最大压料开口 Material press length/maximum material press opening		750mm/600mm	880mm/1250mm
5	剪切刀长度/最大剪切开口 Cutter length/Maximum cutting opening		800mm/535mm	1400mm/760mm
6	剪切料长度（可根据需要调整） Length of sheared material (adjustable)		400mm~900mm	
7	操作方式 Operating mode		PLC控制/遥控操作/自动运行 PLC control/remote operation/Automatic operation	PLC控制/遥控操作/自动运行 PLC control/remote operation/Automatic operation
8	剪切次数 Shearing frequency		2次/分钟 2 times/minute	2次/分钟 2 times/minute
9	剪切能力 Shearing capacity	方钢 Square bar	150*150mm	280*280mm
		圆钢 Round bar	φ150mm	φ310mm

产品规格若有变更，恕不另行通知。We reserve the right to change specifications without prior notice.

